

# STANDARD OUTDOOR 3+1 CCTV CABLES


## INTRODUCTION

The Wirelux CCTV Cable, featuring a hybrid design integrating Communication and Electrical conductors, empowers your surveillance system. Its three Electrical conductors provide power to the CCTV camera, while the communication cable facilitates image recording and communication with control room devices, leveraging the camera's capabilities.

## KEY FEATURES

- Support Hybrid Cable
- Shielded Communication Cable
- Excellent Signaling Characteristics
- UV Resistant
- Supports Outdoor Installations

## SPECIFICATION



	CONDUCTOR TYPE	STRANDED ABC CONDUCTOR	
	POWER CORE CONDUCTOR	NO. OF WIRE/SIZE OF WIRE (NOS./MM)	14/0.100±0.010MM
INSULATION		PVC	
NO OF CORE		3	
COLOUR CODE		RED, GREY & YELLOW	
CORE O.D.		1.35±0.10MM	
VIDEO CORE		CONDUCTOR TYPE	SOLID ABC CONDUCTOR
	NO OF WIRE/SIZE OF WIRE (NOS./MM)	01/0.505±0.005MM	
	INSULATION	PE	
	NO OF CORE	1	
	COLOUR CODE	NATURAL	
	CORE OD.	1.5±0.10MM	
SHIELD	SHIELDED WITH	ALUMINIUM TAPE	
	BRAIDING	ALUMINIUM ALLOY WIRE	
	VIDEO CORE JACKETING	PVC	
	COLOUR OF JACKET	BLACK	
	VIDEO CORE O.D.	2.70±0.10MM	
OUTER SHEATH	SHEATH MATERIAL	PE	
	COLOUR OF JACKET	SUPER BLACK	
	OUTER DIA.	5.70±0.10MM	
	SEQUENTIAL MARKING	EVERY METER	
WEIGHT	WEIGHT OF 90MTR CABLE	2.800±0.020KG	
PACKING	STANDARD LENGTH	90MTRS. IN BOX	
	LOW FREQUENCY PARAMTERS	CONDUCTOR RESISTANCE (DC) OF SOLID CORE	65Ω/KM@20°C Max
		CONDUCTOR RESISTANCE (DC) OF STRANDED CORE	146Ω/100M@20°C Max
		T.S. IN JACKET	NA
ELONGATION IN JACKET		NA	

PRODUCT NO.

CCTV-310D90

DESCRIPTION

STANDARD OUTDOOR CCTV (3+1) -  
90M / Roll or as per Customer Request

COLOR

Super Black or  
as per customer request